



## LS Counterbalance

<b>Unit Model: C912D-365-192 y-series</b>						
<b>Qty. of Cwts</b>	<b>Cwt No.</b>	<b>Weight per Cwt, lbs.</b>	<b>ECB, lbs. @ 192" stroke &amp; max position</b>	<b>ECB, lbs. @ 165" stroke &amp; max position</b>	<b>ECB, lbs. @ 139" stroke &amp; max position</b>	<b>Total dead wt., lbs.</b>
cranks only			4,542	5,243	6,224	
2	7	1,650	7,783	8,941	10,562	3,300
2	6	2,200	8,722	10,013	11,820	4,400
2	5 (3 bolt hole)	2,622	9,400	10,787	12,728	5,244
2	4 (3 bolt hole)	3,247	10,558	12,109	14,279	6,494
4	7	1,650	11,023	12,639	14,900	6,600
2	3 (3 bolt hole)	3,582	11,179	12,817	15,110	7,164
2	2 (3 bolt hole)	4,210	12,064	13,827	16,295	8,420
4	6	2,200	12,902	14,784	17,417	8,800
2	1 (3 bolt hole)	5,280	13,827	15,839	18,655	10,560
4	5 (3 bolt hole)	2,622	14,258	16,332	19,232	10,488
4	4 (3 bolt hole)	3,247	16,574	18,975	22,333	12,988
4	3 (3 bolt hole)	3,582	17,816	20,392	23,995	14,328
4	2 (3 bolt hole)	4,210	19,586	22,412	26,365	16,840
4	1 (3 bolt hole)	5,280	23,112	26,436	31,086	21,120

<b>Unit Model: C912D-365-168, C912D-305-168 y-series</b>						
<b>Qty. of Cwts</b>	<b>Cwt No.</b>	<b>Weight per Cwt, lbs.</b>	<b>ECB, lbs. @ 168" stroke &amp; max position</b>	<b>ECB, lbs. @ 144" stroke &amp; max position</b>	<b>ECB, lbs. @ 121" stroke &amp; max position</b>	<b>Total dead wt., lbs.</b>
cranks only			6,167	6,968	8,091	
2	7	1,650	9,873	11,198	13,052	3,300
2	6	2,200	10,948	12,424	14,491	4,400
2	5 (3 bolt hole)	2,622	11,723	13,309	15,529	5,244
2	4 (3 bolt hole)	3,247	13,047	14,821	17,302	6,494
4	7	1,650	13,578	15,427	18,013	6,600
2	3 (3 bolt hole)	3,582	13,757	15,631	18,253	7,164
2	2 (3 bolt hole)	4,210	14,769	16,786	19,608	8,420
4	6	2,200	15,728	17,880	20,891	8,800
2	1 (3 bolt hole)	5,280	16,786	19,087	22,307	10,560
4	5 (3 bolt hole)	2,622	17,279	19,650	22,967	10,488
4	4 (3 bolt hole)	3,247	19,927	22,673	26,514	12,988
4	3 (3 bolt hole)	3,582	21,347	24,293	28,414	14,328
4	2 (3 bolt hole)	4,210	23,372	26,604	31,125	16,840
4	1 (3 bolt hole)	5,280	27,404	31,206	36,524	21,120