

<b>LS Unit Model</b>	<b>C160D-200-74</b>			
		<b>ECB, lbs.</b>	<b>ECB, lbs.</b>	<b>ECB, lbs.</b>
<b>Qty of Cwts</b>	<b>Cwt position * on crank arm</b>	<b>@74" stroke, at position</b>	<b>@64" stroke, at position</b>	<b>@53" stroke, at position</b>
<b>Counterweight No.:</b>	<b>7 weight: 1,653 lbs</b>			
cranks only		5,019	5,574	6,323
4	10	6,872	7,710	8,841
4	20	8,725	9,847	11,358
4	30	10,579	11,983	13,876
4	40	12,432	14,119	16,393
4	50	15,285	16,256	18,910
4	max 55.4	15,281	17,404	20,263
2	10	5,945	6,642	7,582
2	20	6,872	7,710	8,841
2	30	7,799	8,779	10,100
2	40	8,725	9,847	11,358
2	50	9,652	10,915	12,617
2	max 55.4	10,150	11,489	13,293
<b>Counterweight No.:</b>	<b>8 weight: 1,215 lbs</b>			
cranks only		5,019	5,574	6,323
4	10	6,383	7,147	8,177
4	20	7,748	8,720	10,031
4	30	9,113	10,293	11,885
4	40	10,477	11,866	13,738
4	50	11,842	13,440	15,592
4	max 55.4	13,053	14,836	17,237
2	10	5,701	6,361	7,250
2	20	6,383	7,147	8,177
2	30	7,066	7,934	9,104
2	40	7,748	8,720	10,031
2	50	8,430	9,507	10,958
2	max 55.4	9,036	10,205	11,780