

LS Unit Model	C320D-246-86			
Qty of Cwts	Cwt position * on crank arm	ECB, lbs. @86" stroke, at position	ECB, lbs. @74" stroke, at position	ECB, lbs. @62" stroke, at position
Counterweight No.:	5 (2 bolts)			
cranks only		4,432	4,895	5,389
4	10	7,119	7,976	8,891
4	20	9,806	11,058	12,393
4	30	12,493	14,140	15,895
4	40	15,180	17,221	19,398
4	max 50.4	17,968	20,419	23,031
2	10	5,775	6,436	7,140
2	20	7,119	7,976	8,891
2	30	8,462	9,517	10,642
2	40	9,806	11,058	12,393
2	max 50.4	11,200	12,657	14,210
Counterweight No.:	6 (2 bolts)			
cranks only		4,432	4,895	5,389
4	10	8,723	7,356	8,186
4	20	10,869	9,816	10,982
4	30	13,015	12,277	13,779
4	40	15,161	14,738	16,576
4	max 52.5	15,697	17,814	20,071
2	10	5,505	6,125	6,788
2	20	6,577	7,356	8,186
2	30	7,650	8,586	9,584
2	40	8,723	9,816	10,982
2	max 52.5	10,064	11,354	12,730
Counterweight No.:	7 (2 bolts)			
cranks only		4,432	4,895	5,389
4	10	6,041	6,740	7,487
4	20	7,650	8,586	9,584
4	30	9,260	10,432	11,682
4	40	10,869	12,277	13,779
4	50	12,478	14,123	15,876
4	max 55.4	13,344	15,115	17,004
2	10	5,236	5,818	6,438
2	20	6,041	6,740	7,487
2	30	6,846	7,663	8,535
2	40	7,650	8,586	9,584
2	50	8,455	9,509	10,633
2	max 55.4	8,888	10,005	11,197
Counterweight No.:	8 (2 bolts)			
cranks only		4,432	4,895	5,389
4	10	5,505	6,125	6,788
4	20	6,577	7,356	8,186
4	30	7,650	8,586	9,584
4	40	8,723	9,816	10,982
4	50	9,796	11,047	12,381
4	max 58.9	10,748	12,139	13,622
2	10	4,968	5,510	6,088
2	20	5,505	6,125	6,788
2	30	6,041	6,740	7,487
2	40	6,577	7,356	8,186
2	50	7,114	7,971	8,885
2	max 58.9	7,590	8,517	9,505